



BUILDER TO VERIFY ALL DIMENSIONS & LEVELS ON SITE PRIOR TO ORDERING OF MATERIALS & COMMENCEMENT OF CONSTRUCTION

ALL GUTTER AND DOWNPIPES SIZES AND DETAILS TO HYDRAULIC ENGINEERS DETAILS





MEZZ FLOOR PLAN (TENANCY 1)

SCALE 1:200 @ A3

MEZZ FLOOR PLAN (TENANCY 2)

SCALE 1:200 @ A3

FLOOR PLAN NOTES

ALL CONSTRUCTION TO COMPLY WITH THE NATIONAL CONSTRUCTION CODE OF AUSTRALIA REQUIRMENTS & RELEVANT AUSTRALIAN STANDARDS.

CONTRACTOR TO CONFIRM ALL DIMENSIONS & LEVELS ON SITE PRIOR TO COMMENCEMENT OF ANY WORK INCLUDING BOUNDARY LINES & PEGS.

CONTRACTOR ALSO TO CONFIRM PRESENCE OF ANY EXISTING SERVICES BEFORE COMMENCING WORKS.

DIMENSIONS TAKE PREFERENCE OVER SCALE. DO NOT SCALE OFF DRAWING.

REFER TO CONSULTING ENGINEERS DRAWINGS FOR ALL CIVIL, STRUCTURAL DETAILS & HYDRAULIC ENGINEERS DRAWINGS FOR ALL HYDRAULIC DETAILS.

SHOULD SITE CONDITIONS DIFFER FROM THOSE INDICATED SEEK INSTRUCTIONS FROM DESIGNER.

REFER FLOOR PLAN FOR POSITIONS OF PORTABLE FIRE EXTINGUISHERS & FIXED EMERGENCY LIGHTING

PORTABLE FIRE EXTINGUISHERS TO BE INACCORDANCE WITH NCC E1.6 2016. ADDITIONAL EXTINGUISHERS MAY BE REQUIRED DEPENDING ON TENANCY LAYOUT & ASSOCIATED BUSINESS USES.

MECHANICAL VENTILATION TO AS. 1668.2 & AS/NZS 3666.1 AS INDICATED. MIN 25 \forall s EXHAUST FLOW RATE TO ALL WC'S.

PHYSICAL TERMITE BARRIER SYSTEM TO BE USED IN ACCORDANCE WITH AS, 3660.1, ALL TIMBER TREATED H2/H3 AGAINST TERMITES.

LIGHTING TO AS/NZS 1680.0 & NCC 2016 J6

ALL EXIT DOORS TO COMPLY WITH NCC 2016 CLAUSES D2.10, D2.19 & D2.21 DOOR HARDWARE TO ALL EXIT DOORS TO COMPLY WITH NCC 2016 CLAUSE D2.20

PROVIDE ROOF SAFTEY MESH TO AS/NZS 4389 (1996)

TIMBER/STEEL STUD PARTITIONING TO TOILETS. CEILING HEIGHT 2700mm MIN. WALLS AND CEILING LINED WITH WATER PROOF PLASTERBOARD.

FIX PLASTERBOARD CEILING OVER AMENITY AREAS (TYP) WATERPROOF WET AREAS TO AS 3740.

WATERPROOFING TO WET AREAS TO COMPLY WITH NCC 2016 CLAUSE F1.7 ROOF INSULATION R2.5 "ANTICON" FOIL BACKED FIBRE GLASS INSULATION

PROVIDE NON-COMBUSTIBLE MINERAL FIBRE INSULATION UNDERNEATH ROOF SHEETING TO SEAL ALL FIRE WALLS.

UNISEX ACCESSIBLE FACILITIES TO AS 1428.1, 2009

(CSR BRADFORD FIRE SEAL OR EQUIVALENT)

FIRE HYDRANTS INSTALLED TO ENGINEERS DETAIL. REFER HYDRAULICS ENGINEER DRAWINGS FOR POSITION OF FIRE HYDRANTS

STAIRS, HANDRAILS & BALUSTRADES

ALL STAIRS, HANDRAILS & BALUSTRADES TO COMPLY WITH NCC 2016 PART D2.9, D2.13, D2.14, D2.16 & D2.17 AND AS1428.1 & AS1428.4.

BALUSTRADE POSITIONED MIN 865mm ABOVE NOSING OF TREADS, 1m MIN. ABOVE BALCONY, LANDING OR THE LIKE.

BALUSTRADE REQUIRED TO BOTH SIDES OF STAIR WELLS.
OPENING IN BALUSTRADES TO BE CONSTRUCTED SO A 125mm
SPHERE IS NOT PERMITTED TO PASS THROUGH & FOR A STAIR THE
SPACE TESTED IS ABOVE THE NOSING.

GLAZING INDICATORS

GLAZING INDICATORS TO ENTRY DOORS (75mm WIDE SOLID) TO NCC 2016 D3.12 & AS 1428.1-C16.6 TO DOOR SIDE LIGHTS.

LEGEND

170mm CONCRETE TILT UP WALL TO ENGINEERS DETAILS

90mm INTERNAL STUD WALLS TO ENGINEERS DETAILS

90mm SHS POSTS TO ENGINEERS DETAILS.

EMERGENCY EXITS (TENANCY OVER 300m2):
10 WATT ILUMINATED SINGLE SIDED EXIT
SIGN MODEL E1112,
CLASSIFICATION AS/NZS 2293.1 1998.
LIGHTING TO AS/NZS 1680.0

SF STANLITE SF10 NON-MAINTAINED (10W HALOGEN FIXED FLUSH WITH CEILING) TO AS/NZS 2293.1.

STANLITE BT 136NPR SINGLE 36W NONMAINTAINED OR ALTERNATIVE BRAND TO
SUIT CLASSIFICATION AS 2293:PART 1.
MOUNTED AT 6m MAX ABOVE FINISHED FLOOR.
MECHANICALLY VENTILATED TO AS

MV 1668.2 1991, MIN 25L/S + EXHAUST FLOW RATE. CEILING 2400mm HIGH.

FE

■ EXTINGUISHER TYPE: 3A:40B:(E)
ENSURE FIRE EXTINGUISHERS ARE WITHIN
4m OF 'EXIT' DOOR.
EXTINGUISHER LOCATION SIGN ABOVE IN
ACCORDANCE WITH AS 2444-1995

SINK TGSI/s INSTANTANEOUS HWS IN VERMIN PROOF CABINET UNDER SINK (TYP.)

TACTILE GROUND SURFACE INDICATORS
FIRE HOSE REEL TO ENGINEERS DETAILS

Drawn by SB Checked by DJ BUILDING Client C. MORLEY LOT 27 ACCESS CRESCENT 21.07.17 30.06.17 28.06.17 27.06.17 22.06.17 08.03.17 10.11.16 07.11.16 SB SB SB SB SB SB SB **COOLUM INDUSTRIAL ESTATE** SUN(OAST CLIENTS CHANGE Drawing Description ISSUE DATE SUBJECT INITIAL AUTH MEZZANINE FLOOR PLAN AMENDMENTS 6 LORRAINE AVE, MARCOOLA QLD. 4564 Scale As indicated Date 07.11.16 PHONE:(07)54488 500 Mobile: 0418 715 702 Project No.2016-46 Sheet No. 06 OF 15 EMAIL: buildgreen@bigpond.com **WORKING DWGS** Issue H **QBSA LICENCE No. 65942**

